

Varimat V Bitumen



Our latest addition to the Varimat family, the Varimat V Bitumen, is purpose built with a special roller for overlap welding of bitumen. In addition to speed and temperature, the Varimat V now also displays voltage and welding seam length, ensuring that all the weld parameters are at the optimal set points throughout the welding process.

Benefits

- Precise, durable and easy to operate
- Wrinkle free welding elastomer bitumen
- Independent suspension pressure roller (patented) guarantees even distribution of pressure on uneven surfaces
- Digital temperature display of both actual and set-point values for weld speed and temperature
- Temperature and speed are controlled independently of voltage fluctuations and ambient temperature
- Weld seam width of 40 mm
- Welding speed of 2 to 4 m/min

Why Buy From Us

The Varimat V Bitumen, available in Canada only through STANMECH and its distributor network, is the industry standard for welding roofing membranes. It's ergonomic, easy to program and operate and rugged design makes it the welder of choice for the professional roofer.

Technical Data – Varimat V Bitumen

Voltage	V~	400
Power consumption	W	6300
Amperage	A	15
Frequency	Hz	50 / 60
Temperature	°C	20 - 620
Speed	m/min	0.5 – 5
Welding pressure	N	190
Air flow	%	50 - 100
Pressure Static	Pa	5000 (50mbar)
Emission level	dB	67
Size	mm	640 x 430 x 330
Weight	kg	38 with 5 m cord
Approval mark:	QPS	